



Sikalastic®-670 TC

1-COMPONENT POLYURETHANE TOPCOAT FOR
Sikalastic® ROOF WATERPROOFING SYSTEMS

UNIQUE SELLING POINTS

- Resistant to UV exposure – reflective and resistant to yellowing
- Highly elastic and crack-bridging – retains flexibility even at low temperatures
- Single component, easy to apply
- Easily recoated – no stripping required
- Water vapor permeable
- Good resistance to common atmospheric chemicals

APPLICATION FIELDS:

- UV-stable top coat for Sikalastic® roof waterproofing systems
- Reflective top coat for excellent cool roof characteristics and solar roofs
- Color stable aliphatic PU top coat for use on roofs exposed to ponding water

TECHNICAL CHARACTERISTICS:

- Aliphatic polyurethane
- Packaging: in metal containers of 1kg, 5kg and 20kg
- Color: White (others colors available upon request)
- Consumption: ~0.2-0.6 kg/m² in 1 or 2 coats depending on traffic conditions

Our most current General Sales Conditions shall apply. Please consult the most current local Product Data Sheet prior to any use.

Sika HELLAS ABEE

15 Protomagias str.
GR 145 68, Kryoneri,
Attica, Greece

Contact

Tel. + 30 210 81 60 600
E-mail: export@gr.sika.com
www.sika.gr

BUILDING TRUST

